

WET EVAC QVAC 100

- Fits to a standard ringlock drum.
- Evacs floor spills such as oil, coolants, washing water etc.
- Evacs containers and drums absolutely dry. Empties tanks and drain pits.
- Removes surface decontaminants from process baths.
- For wet vacuuming (with float preventing overfills) or for dry vacuuming.
- Driven with work's compressed air supply.
- Simple and reliable equipment. No moving parts. Maintenance-free.

QVAC 100 is a simple and reliable equipment for vacuuming all types of wet and dry industrial spills. Driven with compressed air and working without moving parts it is very reliable and maintenance-free.

QVAC 100 is vacuuming liquids and particles directly into a standard drum which in turn becomes the carrier for transport to destruction, deposition or recycling. No absorbant materials are used, protecting the environment, saving time and reducing costs for destruction.

Technical Data

Compressed air supply	5 – 7 bar
Air consumption	750 – 1000 l/min
Vacuum	3100 – 3900 mm WS
Noise level at 7 bar	79 dB
Minimum air supply hose diameter	½" for 8 m, ¾" for 60 m and 1" for up to 200 m distance to the compressor.



Wet Evac QVAC 100, scope of supply



QVAC 100 fitted on ringlock drum
(Drum and trolley available from specialist stores)